


# Air Terminal, Imperial Thread



- Lightning strike termination points for use with air terminal bases



Part Number	Diameter Ø	Type	Height H	Thread Size TS	Unit Weight
Material: Aluminum					
LPA221	12.7 mm	Sharp	254.00 mm	1/2 UNC	0.09 kg
LPA221ST	12.7 mm	Blunt	254.00 mm	1/2 UNC	0.09 kg
LPA222	12.7 mm	Sharp	304.80 mm	1/2 UNC	0.10 kg
LPA222ST	12.7 mm	Blunt	304.80 mm	1/2 UNC	0.10 kg
LPA223	12.7 mm	Sharp	381.00 mm	1/2 UNC	0.13 kg
LPA223ST	12.7 mm	Blunt	381.00 mm	1/2 UNC	0.13 kg
LPA224	12.7 mm	Sharp	457.20 mm	1/2 UNC	0.16 kg
LPA224ST	12.7 mm	Blunt	457.20 mm	1/2 UNC	0.16 kg
LPA225	12.7 mm	Sharp	609.60 mm	1/2 UNC	0.21 kg
LPA225ST	12.7 mm	Blunt	609.60 mm	1/2 UNC	0.21 kg
LPA226	12.7 mm	Sharp	762.00 mm	1/2 UNC	0.26 kg
LPA226ST	12.7 mm	Blunt	762.00 mm	1/2 UNC	0.26 kg
LPA227	12.7 mm	Sharp	914.40 mm	1/2 UNC	0.31 kg
LPA227ST	12.7 mm	Blunt	914.40 mm	1/2 UNC	0.31 kg
LPA228	12.7 mm	Sharp	1,219.20 mm	1/2 UNC	0.42 kg
LPA228ST	12.7 mm	Blunt	1,219.20 mm	1/2 UNC	0.42 kg
LPA241	15.9 mm	Sharp	254.00 mm	5/8 UNC	0.14 kg
LPA241ST	15.9 mm	Blunt	254.00 mm	5/8 UNC	0.14 kg
LPA242	15.9 mm	Sharp	304.80 mm	5/8 UNC	0.16 kg
LPA242ST	15.9 mm	Blunt	304.80 mm	5/8 UNC	0.16 kg
LPA243	15.9 mm	Sharp	381.00 mm	5/8 UNC	0.20 kg



Part Number	Diameter Ø	Type	Height H	Thread Size TS	Unit Weight
LPA243ST	15.9 mm	Blunt	381.00 mm	5/8 UNC	0.20 kg
LPA244	15.9 mm	Sharp	457.20 mm	5/8 UNC	0.25 kg
LPA244ST	15.9 mm	Blunt	457.20 mm	5/8 UNC	0.25 kg
LPA245	15.9 mm	Sharp	609.60 mm	5/8 UNC	0.33 kg
LPA245ST	15.9 mm	Blunt	609.60 mm	5/8 UNC	0.33 kg
LPA246	15.9 mm	Sharp	762.00 mm	5/8 UNC	0.41 kg
LPA246ST	15.9 mm	Blunt	762.00 mm	5/8 UNC	0.41 kg
LPA247	15.9 mm	Sharp	914.40 mm	5/8 UNC	0.49 kg
LPA247ST	15.9 mm	Blunt	914.40 mm	5/8 UNC	0.49 kg
LPA248	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	0.65 kg
LPA248ST	15.9 mm	Blunt	1,219.20 mm	5/8 UNC	0.65 kg
<b>Material: Copper – Finish: Bare</b>					
LPC201B	9.5 mm	Sharp	254.00 mm	3/8 UNC	0.16 kg
LPC201BST	9.5 mm	Blunt	254.00 mm	3/8 UNC	0.16 kg
LPC202B	9.5 mm	Sharp	304.80 mm	3/8 UNC	0.19 kg
LPC202BST	9.5 mm	Blunt	304.80 mm	3/8 UNC	0.19 kg
LPC203B	9.5 mm	Sharp	381.00 mm	3/8 UNC	0.23 kg
LPC203BST	9.5 mm	Blunt	381.00 mm	3/8 UNC	0.23 kg
LPC204B	9.5 mm	Sharp	457.20 mm	3/8 UNC	0.28 kg
LPC204BST	9.5 mm	Blunt	457.20 mm	3/8 UNC	0.28 kg
LPC205B	9.5 mm	Sharp	609.60 mm	3/8 UNC	0.37 kg
LPC205BST	9.5 mm	Blunt	609.60 mm	3/8 UNC	0.37 kg
LPC206B	9.5 mm	Sharp	762.00 mm	3/8 UNC	0.47 kg
LPC206BST	9.5 mm	Blunt	762.00 mm	3/8 UNC	0.47 kg
LPC207B	9.5 mm	Sharp	914.40 mm	3/8 UNC	0.56 kg
LPC207BST	9.5 mm	Blunt	914.40 mm	3/8 UNC	0.56 kg
LPC208B	9.5 mm	Sharp	1,219.20 mm	3/8 UNC	0.75 kg
LPC208BST	9.5 mm	Blunt	1,219.20 mm	3/8 UNC	0.75 kg
LPC221B	12.7 mm	Sharp	254.00 mm	1/2 UNC	0.28 kg
LPC221BST	12.7 mm	Blunt	254.00 mm	1/2 UNC	0.28 kg
LPC222B	12.7 mm	Sharp	304.80 mm	1/2 UNC	0.33 kg
LPC222BST	12.7 mm	Blunt	304.80 mm	1/2 UNC	0.33 kg
LPC223B	12.7 mm	Sharp	381.00 mm	1/2 UNC	0.41 kg
LPC223BST	12.7 mm	Blunt	381.00 mm	1/2 UNC	0.41 kg
LPC224B	12.7 mm	Sharp	457.20 mm	1/2 UNC	0.50 kg
LPC224BST	12.7 mm	Blunt	457.20 mm	1/2 UNC	0.50 kg
LPC225B	12.7 mm	Sharp	609.60 mm	1/2 UNC	0.66 kg
LPC225BST	12.7 mm	Blunt	609.60 mm	1/2 UNC	0.66 kg
LPC226B	12.7 mm	Sharp	762.00 mm	1/2 UNC	0.83 kg
LPC226BST	12.7 mm	Blunt	762.00 mm	1/2 UNC	0.83 kg
LPC227B	12.7 mm	Sharp	914.40 mm	1/2 UNC	0.99 kg
LPC227BST	12.7 mm	Blunt	914.40 mm	1/2 UNC	0.99 kg
LPC228B	12.7 mm	Sharp	1,219.20 mm	1/2 UNC	1.32 kg
LPC228BST	12.7 mm	Blunt	1,219.20 mm	1/2 UNC	1.32 kg
LPC241B	15.9 mm	Sharp	254.00 mm	5/8 UNC	0.43 kg
LPC241BST	15.9 mm	Blunt	254.00 mm	5/8 UNC	0.43 kg
LPC242B	15.9 mm	Sharp	304.80 mm	5/8 UNC	0.52 kg
LPC242BST	15.9 mm	Blunt	304.80 mm	5/8 UNC	0.52 kg
LPC243B	15.9 mm	Sharp	381.00 mm	5/8 UNC	0.52 kg



Part Number	Diameter Ø	Type	Height H	Thread Size TS	Unit Weight
LPC243BST	15.9 mm	Blunt	381.00 mm	5/8 UNC	0.65 kg
LPC244B	15.9 mm	Sharp	457.20 mm	5/8 UNC	0.65 kg
LPC244BST	15.9 mm	Blunt	457.20 mm	5/8 UNC	0.65 kg
LPC244MBST	15.9 mm	Blunt	500.38 mm	5/8 UNC	0.85 kg
LPC245B	15.9 mm	Sharp	609.60 mm	5/8 UNC	0.78 kg
LPC245BST	15.9 mm	Blunt	609.60 mm	5/8 UNC	0.78 kg
LPC246B	15.9 mm	Sharp	762.00 mm	5/8 UNC	1.03 kg
LPC246BST	15.9 mm	Blunt	762.00 mm	5/8 UNC	1.03 kg
LPC247B	15.9 mm	Sharp	914.40 mm	5/8 UNC	1.29 kg
LPC247BST	15.9 mm	Blunt	914.40 mm	5/8 UNC	1.29 kg
LPC247MBST	15.9 mm	Blunt	1,000.76 mm	5/8 UNC	1.70 kg
LPC248B	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	2.07 kg
LPC248BST	15.9 mm	Blunt	1,219.20 mm	5/8 UNC	2.07 kg
LPC415	15.9 mm	Sharp	1,524.00 mm	5/8 UNC	2.59 kg
LPC416	15.9 mm	Sharp	1,828.80 mm	5/8 UNC	3.10 kg
LPC417	15.9 mm	Sharp	2,133.60 mm	5/8 UNC	3.62 kg
LPC418	15.9 mm	Sharp	2,438.40 mm	5/8 UNC	4.14 kg
LPC421	19.1 mm	Sharp	457.20 mm	5/8 UNC	0.78 kg
LPC422	19.1 mm	Sharp	609.60 mm	5/8 UNC	1.03 kg
LPC423	19.1 mm	Sharp	914.40 mm	5/8 UNC	1.55 kg
LPC424	19.1 mm	Sharp	1,219.20 mm	5/8 UNC	2.07 kg
LPC425	19.1 mm	Sharp	1,524.00 mm	5/8 UNC	2.59 kg
LPC426	19.1 mm	Sharp	1,828.80 mm	5/8 UNC	3.10 kg
LPC427	19.1 mm	Sharp	2,133.60 mm	5/8 UNC	3.62 kg
LPC428	19.1 mm	Sharp	2,438.40 mm	5/8 UNC	4.14 kg
<b>Material: Copper – Finish: Lead Covered</b>					
LPLC411	15.9 mm	Sharp	457.20 mm	5/8 UNC	1.11 kg
LPLC412	15.9 mm	Sharp	609.60 mm	5/8 UNC	1.48 kg
LPLC413	15.9 mm	Sharp	914.40 mm	5/8 UNC	2.54 kg
LPLC414	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	2.76 kg
LPLC415	15.9 mm	Sharp	1,524.00 mm	5/8 UNC	4.32 kg
LPLC416	15.9 mm	Sharp	1,828.80 mm	5/8 UNC	5.20 kg
LPLC417	15.9 mm	Sharp	2,133.60 mm	5/8 UNC	6.07 kg
LPLC418	15.9 mm	Sharp	2,438.40 mm	5/8 UNC	6.94 kg
LPLC422	19.1 mm	Sharp	609.60 mm	5/8 UNC	2.28 kg
LPLC425	19.1 mm	Sharp	1,524.00 mm	5/8 UNC	5.71 kg
LPLC426	19.1 mm	Sharp	1,828.80 mm	5/8 UNC	6.85 kg
LPLC427	19.1 mm	Sharp	2,133.60 mm	5/8 UNC	7.99 kg
LPLC428	19.1 mm	Sharp	2,438.40 mm	5/8 UNC	9.13 kg
<b>Material: Copper – Finish: Nickel Plated</b>					
LPC201	9.5 mm	Sharp	254.00 mm	3/8 UNC	0.16 kg
LPC201ST	9.5 mm	Blunt	254.00 mm	3/8 UNC	0.19 kg
LPC202	9.5 mm	Sharp	304.80 mm	3/8 UNC	0.19 kg
LPC202ST	9.5 mm	Blunt	304.80 mm	3/8 UNC	0.19 kg
LPC203	9.5 mm	Sharp	381.00 mm	3/8 UNC	0.23 kg
LPC203ST	9.5 mm	Blunt	381.00 mm	3/8 UNC	0.23 kg
LPC204	9.5 mm	Sharp	457.20 mm	3/8 UNC	0.28 kg
LPC204ST	9.5 mm	Blunt	457.20 mm	3/8 UNC	0.28 kg
LPC205	9.5 mm	Sharp	609.60 mm	3/8 UNC	0.37 kg



Part Number	Diameter Ø	Type	Height H	Thread Size TS	Unit Weight
LPC205ST	9.5 mm	Blunt	609.60 mm	3/8 UNC	0.37 kg
LPC206	9.5 mm	Sharp	762.00 mm	3/8 UNC	0.47 kg
LPC206ST	9.5 mm	Blunt	762.00 mm	3/8 UNC	0.47 kg
LPC207	9.5 mm	Sharp	914.40 mm	3/8 UNC	0.56 kg
LPC207ST	9.5 mm	Blunt	914.40 mm	3/8 UNC	0.56 kg
LPC208	9.5 mm	Sharp	1,219.20 mm	3/8 UNC	0.75 kg
LPC208ST	9.5 mm	Blunt	1,219.20 mm	3/8 UNC	0.75 kg
LPC221	12.7 mm	Sharp	254.00 mm	1/2 UNC	0.28 kg
LPC221ST	12.7 mm	Blunt	254.00 mm	1/2 UNC	0.33 kg
LPC222	12.7 mm	Sharp	304.80 mm	1/2 UNC	0.33 kg
LPC222ST	12.7 mm	Blunt	304.80 mm	1/2 UNC	0.33 kg
LPC223	12.7 mm	Sharp	381.00 mm	1/2 UNC	0.41 kg
LPC223ST	12.7 mm	Blunt	381.00 mm	1/2 UNC	0.41 kg
LPC224	12.7 mm	Sharp	457.20 mm	1/2 UNC	0.50 kg
LPC224ST	12.7 mm	Blunt	457.20 mm	1/2 UNC	0.50 kg
LPC225	12.7 mm	Sharp	609.60 mm	1/2 UNC	0.66 kg
LPC225ST	12.7 mm	Blunt	609.60 mm	1/2 UNC	0.66 kg
LPC226	12.7 mm	Sharp	762.00 mm	1/2 UNC	0.83 kg
LPC226ST	12.7 mm	Blunt	762.00 mm	1/2 UNC	0.83 kg
LPC227	12.7 mm	Sharp	914.40 mm	1/2 UNC	0.99 kg
LPC227ST	12.7 mm	Blunt	914.40 mm	1/2 UNC	0.99 kg
LPC228	12.7 mm	Sharp	1,219.20 mm	1/2 UNC	1.32 kg
LPC228ST	12.7 mm	Blunt	1,219.20 mm	1/2 UNC	1.32 kg
LPC241	15.9 mm	Sharp	254.00 mm	5/8 UNC	0.43 kg
LPC241ST	15.9 mm	Blunt	254.00 mm	5/8 UNC	0.43 kg
LPC242	15.9 mm	Sharp	304.80 mm	5/8 UNC	0.43 kg
LPC242ST	15.9 mm	Blunt	304.80 mm	5/8 UNC	0.52 kg
LPC243	15.9 mm	Sharp	381.00 mm	5/8 UNC	0.52 kg
LPC243ST	15.9 mm	Blunt	381.00 mm	5/8 UNC	0.65 kg
LPC244	15.9 mm	Sharp	457.20 mm	5/8 UNC	0.65 kg
LPC244ST	15.9 mm	Blunt	457.20 mm	5/8 UNC	0.78 kg
LPC245	15.9 mm	Sharp	609.60 mm	5/8 UNC	0.78 kg
LPC245ST	15.9 mm	Blunt	609.60 mm	5/8 UNC	1.03 kg
LPC246	15.9 mm	Sharp	762.00 mm	5/8 UNC	1.03 kg
LPC246ST	15.9 mm	Blunt	762.00 mm	5/8 UNC	1.03 kg
LPC247	15.9 mm	Sharp	914.40 mm	5/8 UNC	1.29 kg
LPC247ST	15.9 mm	Blunt	1,219.20 mm	5/8 UNC	2.07 kg
LPC248	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	2.07 kg
LPC248ST	15.9 mm	Blunt	1,219.20 mm	5/8 UNC	2.07 kg
<b>Material: Copper – Finish: Tinned</b>					
LPC201L	9.5 mm	Sharp	254.00 mm	3/8 UNC	0.16 kg
LPC201LST	9.5 mm	Blunt	254.00 mm	3/8 UNC	0.16 kg
LPC202L	9.5 mm	Sharp	304.80 mm	3/8 UNC	0.19 kg
LPC202LST	9.5 mm	Blunt	304.80 mm	3/8 UNC	0.19 kg
LPC203L	9.5 mm	Sharp	381.00 mm	3/8 UNC	0.23 kg
LPC203LST	9.5 mm	Blunt	381.00 mm	3/8 UNC	0.23 kg
LPC204L	9.5 mm	Sharp	457.20 mm	3/8 UNC	0.28 kg
LPC204LST	9.5 mm	Blunt	457.20 mm	3/8 UNC	0.28 kg
LPC205L	9.5 mm	Sharp	609.60 mm	3/8 UNC	0.37 kg



Part Number	Diameter Ø	Type	Height H	Thread Size TS	Unit Weight
LPC205LST	9.5 mm	Blunt	609.60 mm	3/8 UNC	0.37 kg
LPC206L	9.5 mm	Sharp	762.00 mm	3/8 UNC	0.47 kg
LPC206LST	9.5 mm	Blunt	762.00 mm	3/8 UNC	0.47 kg
LPC207L	9.5 mm	Sharp	914.40 mm	3/8 UNC	0.56 kg
LPC207LST	9.5 mm	Blunt	914.40 mm	3/8 UNC	0.56 kg
LPC208L	9.5 mm	Sharp	1,219.20 mm	3/8 UNC	0.75 kg
LPC208LST	9.5 mm	Blunt	1,219.20 mm	3/8 UNC	0.75 kg
LPC221L	12.7 mm	Sharp	254.00 mm	1/2 UNC	0.28 kg
LPC221LST	12.7 mm	Blunt	254.00 mm	1/2 UNC	0.28 kg
LPC222L	12.7 mm	Sharp	304.80 mm	1/2 UNC	0.33 kg
LPC222LST	12.7 mm	Blunt	304.80 mm	1/2 UNC	0.33 kg
LPC223L	12.7 mm	Sharp	381.00 mm	1/2 UNC	0.41 kg
LPC223LST	12.7 mm	Blunt	381.00 mm	1/2 UNC	0.41 kg
LPC224L	12.7 mm	Sharp	457.20 mm	1/2 UNC	0.50 kg
LPC224LST	12.7 mm	Blunt	457.20 mm	1/2 UNC	0.50 kg
LPC225L	12.7 mm	Sharp	609.60 mm	1/2 UNC	0.66 kg
LPC225LST	12.7 mm	Blunt	609.60 mm	1/2 UNC	0.66 kg
LPC226L	12.7 mm	Sharp	762.00 mm	1/2 UNC	0.83 kg
LPC226LST	12.7 mm	Blunt	762.00 mm	1/2 UNC	0.83 kg
LPC227L	12.7 mm	Sharp	914.40 mm	1/2 UNC	0.99 kg
LPC227LST	12.7 mm	Blunt	914.40 mm	1/2 UNC	0.99 kg
LPC228L	12.7 mm	Sharp	1,219.20 mm	1/2 UNC	1.32 kg
LPC228LST	12.7 mm	Blunt	1,219.20 mm	1/2 UNC	1.32 kg
LPC242L	15.9 mm	Sharp	304.80 mm	5/8 UNC	0.52 kg
LPC242LST	15.9 mm	Blunt	304.80 mm	5/8 UNC	0.52 kg
LPC244L	15.9 mm	Sharp	457.20 mm	5/8 UNC	0.65 kg
LPC244LST	15.9 mm	Blunt	457.20 mm	5/8 UNC	0.78 kg
LPC245L	15.9 mm	Sharp	609.60 mm	5/8 UNC	1.03 kg
LPC245LST	15.9 mm	Blunt	609.60 mm	5/8 UNC	1.03 kg
LPC247L	15.9 mm	Sharp	914.40 mm	5/8 UNC	1.29 kg
LPC247LST	15.9 mm	Blunt	914.40 mm	5/8 UNC	1.29 kg
LPC248L	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	2.07 kg
<b>Material: Stainless Steel 304</b>					
LPS222	15.9 mm	Sharp	304.80 mm	5/8 UNC	0.48 kg
LPS223	15.9 mm	Sharp	381.00 mm	5/8 UNC	0.59 kg
LPS224	15.9 mm	Sharp	457.20 mm	5/8 UNC	0.71 kg
LPS224ST	15.9 mm	Blunt	457.20 mm	5/8 UNC	0.71 kg
LPS225	15.9 mm	Sharp	609.60 mm	5/8 UNC	0.95 kg
LPS225ST	15.9 mm	Blunt	609.60 mm	5/8 UNC	0.95 kg
LPS226	15.9 mm	Sharp	762.00 mm	5/8 UNC	1.19 kg
LPS227	15.9 mm	Sharp	914.40 mm	5/8 UNC	1.43 kg
LPS227ST	15.9 mm	Blunt	914.40 mm	5/8 UNC	1.43 kg
LPS228	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	1.90 kg
LPS411	15.9 mm	Sharp	457.20 mm	5/8 UNC	0.71 kg
LPS412	15.9 mm	Sharp	609.60 mm	5/8 UNC	0.95 kg
LPS413	15.9 mm	Sharp	914.40 mm	5/8 UNC	1.43 kg
LPS414	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	1.90 kg
LPS415	15.9 mm	Sharp	1,524.00 mm	5/8 UNC	2.38 kg
LPS416	15.9 mm	Sharp	1,828.80 mm	5/8 UNC	2.85 kg



Part Number	Diameter Ø	Type	Height H	Thread Size TS	Unit Weight
LPS417	15.9 mm	Sharp	2,133.60 mm	5/8 UNC	3.33 kg
LPS418	15.9 mm	Sharp	2,438.40 mm	5/8 UNC	3.81 kg
LPS421	15.9 mm	Sharp	457.20 mm	5/8 UNC	0.71 kg
LPS422	15.9 mm	Sharp	609.60 mm	5/8 UNC	0.95 kg
LPS423	15.9 mm	Sharp	914.40 mm	5/8 UNC	1.43 kg
LPS424	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	1.90 kg
LPS425	15.9 mm	Sharp	1,524.00 mm	5/8 UNC	2.38 kg
LPS426	15.9 mm	Sharp	1,828.80 mm	5/8 UNC	2.85 kg
LPS427	15.9 mm	Sharp	2,133.60 mm	5/8 UNC	3.33 kg
LPS428	15.9 mm	Sharp	2,438.40 mm	5/8 UNC	3.81 kg
<b>Material: Stainless Steel 316</b>					
LPS414XT316	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	1.90 kg
LPS415XT316	15.9 mm	Sharp	1,524.00 mm	5/8 UNC	2.38 kg
LPS416XT316	15.9 mm	Sharp	1,828.80 mm	5/8 UNC	2.85 kg
LPS417XT316	15.9 mm	Sharp	2,133.60 mm	5/8 UNC	3.33 kg
LPS422XT316	15.9 mm	Sharp	609.60 mm	5/8 UNC	0.95 kg
LPS424XT316	15.9 mm	Sharp	1,219.20 mm	5/8 UNC	1.90 kg
LPS426XT316	15.9 mm	Sharp	1,828.80 mm	5/8 UNC	2.85 kg

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

