

Air Terminal Base, Vertical Mount with Offset, Imperial Thread



- For use on vertical surfaces
- Offset provides clearance for overhang of wall cap or cover
- Accommodates vertical or horizontal cable runs
- For positive bolt tension cable clamping





Conductor Size, UL: Class 1 - Class 2 (4/0 Max)



Part Number	Thread Size TS	Depth D	Height H	Width W	Hole Size HS	А	Unit Weight
Material: Aluminum – Finish: Bare							
LPA31912	1/2 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.132 kg
LPA31958	5/8 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.132 kg
Material: Copper – Finish: Bare							
LPC31938	3/8 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.376 kg
LPC31912	1/2 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.376 kg
LPC31958	5/8 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.376 kg
Material: Copper – Finish: Tinned							
LPC319L38	3/8 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.376 kg
LPC319L12	1/2 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.376 kg
LPC319L58	5/8 UNC	59.53 mm	79.38 mm	79.375 mm	12.7 mm	38.1 mm	0.376 kg

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved. CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.



