




C-EU Single Cable to Flange Clamp



- Supports single run of conduit
- Attaches to beam flanges, angle iron, joists and other structural supports



Material: Steel
Finish: Hot-Dip Galvanized

Part Number	Article Number	Outer Diameter OD	Flange Thickness FT	A	Torque TQ
C12EU	337300	6 – 12 mm	12 mm Max	41 mm Max	2 N-m
C16EU	337310	12 – 16 mm	12 mm Max	46 mm Max	2 N-m
C20EU	337320	16 – 20 mm	12 mm Max	50 mm Max	2 N-m
C32EU	337350	28 – 32 mm	12 mm Max	63 mm Max	2 N-m
C44EU	337380	40 – 44 mm	12 mm Max	81 mm Max	4 N-m
C82EU	337460	76 – 82 mm	12 mm Max	119 mm Max	4 N-m
C88EU	337470	82 – 88 mm	12 mm Max	125 mm Max	4 N-m
C94EU	337480	88 – 94 mm	12 mm Max	131 mm Max	4 N-m
C100EU	337490	94 – 100 mm	12 mm Max	137 mm Max	4 N-m

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

