


Through Roof Assembly, Air Terminal, Swivel to Parallel Conductor



- Allows for lightning protection conductors to be concealed in ceiling or walls



Conductor Size, UL: Class 1 - Class 2 (4/0 Max)

Part Number	Connection Material, Air Terminal	Connection Material, Parallel Conductor	Thread Size TS	Rod Length L	Rod Size RS	Unit Weight
Material: Aluminum, Copper, Stainless Steel 18-8						
LPC628A12	Aluminum	Copper	1/2 UNC	304.8 mm	1/2 "	0.633 kg
LPC628A58	Aluminum	Copper	5/8 UNC	304.8 mm	1/2 "	0.633 kg
Material: Aluminum, Stainless Steel 18-8						
LPA62812	Aluminum	Aluminum	1/2 UNC	304.8 mm	1/2 "	0.435 kg
LPA62858	Aluminum	Aluminum	5/8 UNC	304.8 mm	1/2 "	0.435 kg
Material: Copper, Stainless Steel 18-8						
LPC62838	Copper	Copper	3/8 UNC	304.8 mm	1/2 "	0.633 kg
LPC62812	Copper	Copper	1/2 UNC	304.8 mm	1/2 "	0.633 kg
LPC62858	Copper	Copper	5/8 UNC	304.8 mm	1/2 "	0.633 kg

Always consult the roof manufacturer or owner for proper flashing materials.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

