


Through Roof Assembly, Air Terminal to In-Line Conductor



- Allows for lightning protection conductors to be concealed in ceiling or walls



Conductor Size, UL: Class 1 - Class 2 (4/0 Max)

Part Number	Connection Material, Air Terminal	Connection Material, In-Line Conductor	Thread Size TS	Rod Length L	Rod Size RS	Unit Weight
Material: Aluminum, Copper, Stainless Steel 18-8						
LPC626A12	Aluminum	Copper	1/2 UNC	304.8 m	1/2 "	0.485 kg
LPC626A58	Aluminum	Copper	5/8 UNC	304.8 m	1/2 "	0.485 kg
Material: Aluminum, Stainless Steel 18-8						
LPA62612	Aluminum	Aluminum	1/2 UNC	304.8 m	1/2 "	0.485 kg
Material: Copper, Stainless Steel 18-8						
LPC62638	Copper	Copper	3/8 UNC	304.8 m	1/2 "	0.485 kg
LPC62612	Copper	Copper	1/2 UNC	304.8 m	1/2 "	0.485 kg
LPC62658	Copper	Copper	5/8 UNC	304.8 m	1/2 "	0.485 kg

Always consult the roof manufacturer or owner for proper flashing materials.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

