


Female-Male Swivel Adaptor, Imperial Thread



- Allows air terminal to be positioned vertically when base is on a sloping roof
- Male thread includes locknut for positioning



Part Number	Article Number	Thread Size 1 TS1	Thread Size 2 TS2	Length 1 L1	Length 2 L2	Unit Weight
Material: Aluminum						
LPA2832F2M	–	1/2 UNC	1/2 UNC	44.5 mm	69.9 mm	0.068 kg
LPA2842F5M	–	1/2 UNC	5/8 UNC	44.5 mm	69.9 mm	0.068 kg
LPA2845F2M	–	5/8 UNC	1/2 UNC	44.5 mm	69.9 mm	0.068 kg
LPA2855F5M	–	5/8 UNC	5/8 UNC	44.5 mm	69.9 mm	0.068 kg
Material: Copper						
LPC2813F3M	701974	3/8 UNC	3/8 UNC	44.5 mm	69.9 mm	0.231 kg
LPC2823F2M	–	3/8 UNC	1/2 UNC	44.5 mm	69.9 mm	0.231 kg
LPC2822F3M	–	1/2 UNC	3/8 UNC	44.5 mm	69.9 mm	0.231 kg
LPC2832F2M	–	1/2 UNC	1/2 UNC	44.5 mm	69.9 mm	0.231 kg
LPC2842F5M	–	1/2 UNC	5/8 UNC	44.5 mm	69.9 mm	0.231 kg
LPC2845F2M	–	5/8 UNC	1/2 UNC	44.5 mm	69.9 mm	0.231 kg
LPC2855F5M	–	5/8 UNC	5/8 UNC	44.5 mm	69.9 mm	0.231 kg
Material: Copper – Finish: Tinned						
LPC281L3F3M	–	3/8 UNC	3/8 UNC	44.5 mm	69.9 mm	0.231 kg
Material: Stainless Steel 304						
LPS2832F2M	–	1/2 UNC	1/2 UNC	44.5 mm	69.9 mm	0.218 kg
LPS2845F2M	–	5/8 UNC	1/2 UNC	44.5 mm	69.9 mm	0.218 kg
LPS2855F5M	–	5/8 UNC	5/8 UNC	44.5 mm	69.9 mm	0.218 kg



UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

